



STEINFURTH AUTO-SAMPLER 380C-PET

...for automatic pressurized multiple sampling



Routine sampling from beverage containers for analytical purposes may result in considerable strain for additional laboratory work. While sampling consists of a few simple movements, these have to be attentively performed and often every few minutes interrupt other tasks that require full concentration. Especially if great numbers of samples must be taken and the main analytical work is already semi-automated, manual operation of a sampling device poses an additional work time (= costs).

The Steinfurth Auto-Sampler AS 380C offers high efficient integration of measuring devices requiring beverage sampling with automatic multiple sampling from up to 12 containers.

BENEFITS:

- Quick return of investment
- Easy automatic operation and loading
- Cost efficient multiple sampling/measurement
- Integration of stand alone measuring instruments to automatic operated "Mini Lab"
- Automatic adaptation to different container sizes
- Time (= cost) reduction on QC operations
- Optional automatic sample scanning and data transfer to the LIMS

OPERATION:

The PET containers are conveyed to an automatic piercing device which pierces the bottle closure and lowers a sampling probe into the liquid through which the sample is fed to the analyzer connected to the Auto-Sampler. A certain sampling pressure is maintained all the time and prevents the sample from foaming or CO₂ loss.

A safety cabinet protects the user from injury hazards due to moving parts and from package fragments.

The Auto-Sampler AS 380C is able to communicate with analyzers like the Steinfurth Foam Stability Tester or flow through instruments (for CO₂, O₂, density...) via the Steinfurth Interface, synchronising automatic sampling and measuring.

TECHNICAL DATA:

Max. Container size:	up to 3 liter
Container types:	PET bottles
Power supply:	230 or 115 VAC
Compressed air supply:	7 bars / 101.5psi